

Spider

USB and **SIP/IP** Telephone

MT505



Enhanced audio conferencing, simplified.

Change the way you conference with the Spider. Featuring state of the art acoustics, noise and echo cancellation technologies and a proprietary portfolio of algorithms, the Spider is the most powerful and advanced conference phone on the market. The four powerful microphones, true HD Audio, full duplex, and exceptional broadcasting range ensure crystal-clear, seamless conversations.

The Spider addresses all your audio needs in the conference room.

Designed with both telephone connectivity and a PC soft interface for video conferencing, the Spider eliminates the need for two separate conferencing devices to be placed in your conference room or office. Use the Spider alone or connected to up to 14 daisy chain units to cover any size conference room design.

FEATURES

- Bridging between USB and VoIP/SIP/IP
- Daisy Chainable up to 14 slave units
- · Interactive dial pad
- Four microphone beamforming array with directional LED lighting
- Full duplex communication
- DSP based algorithms
 Echo canceling
 Noise reduction
 De-reverb
 - Automatic gain control
- Supports PoE (Power over Ethernet)

info@phnxaudio.com www.**phnxaudio**.com



The Ideal Audio Conference Solution For:

- Conference rooms of any size
- Training Rooms and Classrooms
- Huddle and Breakout Rooms
- Executive Offices

Performance: A state-of-the-art acoustic design that delivers a pick up range and speaker clarity like no other conference phone on the market. The Spider's powerful DSP accompanied by Phoenix Audio Technologies' proprietary algorithms provides best in class echo-cancellation, noise suppression and a true HD audio experience.

Intuitive User Interface: The Spider is the first conference phone that you can see what your audio device is doing during the conference call. With discreetly placed LED lights and an interactive dial pad that both come to life when the Spider is in action.

Expand: The Spider supports power daisy chaining of up to 14 slave units to cover any size conference room. The cable connectivity is conveniently placed under the unit for a sleek look in your conference room.

Connect: The Spider is designed to fulfill your every conference room audio need. With the capability to connect to your telephony line and video codec simultaneously and perform a three way call bridge. With the Spider there is no more need for multiple audio solutions for one conference room.

SPECIFICATIONS

Connections

SIP/IP with USB Interface (mini B connector) 3.5mm DIN, 4 pole for external microphone and speaker connection

Ethernet daisy chain expandability of up to

Power Consumption: 150 mA from 48V ac/dc adaptor or via POE supply.

Frequency Response 50Hz - 16KHz Low latency (10ms) Broadcast level (peak): 92dB SPL @1m (5 watts RMS) Three-way bridging capability Noise cancelation > 10dB (without pumping

100% full duplex - no attenuation (in either

direction) during full duplex High-end performance confirms to ITU-T G.167

Acoustic echo cancelation > 40dB/sec Residual echo is suppressed to the environment noise level, preventing artificial ducking of signal

4 high-quality directional microphones Beam-forming algorithm (forms and directs audio beams towards a defined direction) Automatic voice-level adjustment (AGC)

Dimensions

Dimension: 7" diameter, 1-7/8" height Weight: 2 lbs Metal case and metal grill mesh for high RFI immunity and product durability High RFI immunity and product durability

VoIP and Signaling

SIP -RFC 3261, SDP - RFC 2327 SIP over TCP/UDP, Redundancy, Digest Authentication, PRACK, Early Media

Data Protocols

IPv4, TCP, UDP, ICMP, ARP, RTP, SRTP, Static IP/DHCP IP Assignment, IEEE 802.1p/Q. HTTP/HTTPS/DHCP,NTP, FTP/TFTP

Software

Plug-and-Play - No installation or additional drivers required

Audio Setup Utility is available for Windows

Recording utility is available for Windows. Recording utility allows you to record conversations to your computer via the device. Operating systems: Windows 98 and up / Linux / MacOS.

Accessories

USB cable 48V power supply International AC adapter Daisy chain cable (Ethernet) Telephone cable

Warranty

Two Years.

Provisioning and Management

Web Server for Configuration and Management, COnfiguration update via FTP, TFTP, HTTP, HTTPS, DHCP Options (66, 67, 160, 12, 77, 42)









